## SOUNDCAM ULTRA SENSOR



Product data

#### Highlights

- Real-time results at 100 fps
- IP54 protection
- Audible and ultrasound range
- Streaming via Ethernet (TCP/IP)
- Analysis up to 100 kHz

#### **Applications**

- Road/traffic monitoring
- EOL testing/quality assurance
- Condition based monitoring
- Non destructive testing
- Partial discharge localization



# SOUNDCAM ULTRA SENSOR

**The First Sound Camera Sensor for Integration** 



### What is SoundCam?

The SoundCam Ultra Sensor is an acoustic camera covering the audible and ultrasonic frequency ranges. It has a USB and an ethernet interface, which allow connection to a remote PC. The supplied PC software will show the location of acoustic events in real-time at up to 100fps, overlaid on the camera image.

One or more of these sensors can be combined into your own applications to form complex machine monitoring, leak detection, or animal or traffic monitoring networks, for example. Since the ultrasonic range is also included, electrical discharge or sparking can be monitored over vast networks.

The light weight, compact and waterproofed design makes it highly suitable for drone use. No other acoustic camera is so small and flexible, opening up infinite possibilities for new applications!





Hardware			
Physical Properties	Dimensions	15 x 15 x 7.5 cm (5.9 x 5.9 x 2.9 inch)	
	Weight	1.9 kg (4.4 lb)	
	Waterproof	IP54	
	Housing	Aluminium	
	Mounting	4 x M6	
	Operating temp	-20°C to 50°C (-4°F to 122°F)	
	Storage temp	-30°C to 60°C (-22°F to 140°F)	
Interfaces	USB	data streaming and firmware updates	
	Ethernet	LAN for data streaming	
Sensors	Microphones	72 digital MEMS	
	Frequency range	Up to 100 kHz	
	Sample rate	200 kHz	
	Sound pressure	Max. 120 dB	
	Resolution	24 bit	
Optical Camera	Туре	Digital	
	Resolution	320x240 (50fps) or 640x480 (16fps)	
	Aperture angle	70° (FoV horizontal)	
	Shutter	Global shutter	
Output		Acoustic map video	
		Video	
		Local sound	
		Audio spectrum	
Communi-	Logical	TCP/IP	
cation	Physical	Ethernet or USB-B	
Power	Input	9 - 19V with power adapter	

	Software features		
OS	Windows (for Laptop/PC)		
HMI	Keyboard, mouse, headphones		
Protection	Password (unauthorized access protection)		
Online Performance	Up to 100 acoustic fps, up to 50 optical fps		
	Acoustic pictures, optical pictures, FFT and spectrogram		
	Listen to local sound (broadband or frequency filtered)		
	Place marker while measuring		
	Buffer recording, trigger recording (SPL or frequency)		
	Long term measurements (average and peak-hold)		
	Time weighting: fast, slow, impulse		
Offline Features	View acoustic results frame by frame		
	Save and reload		
	Replay in real-time or slow motion		
	Listen to local sound		
Export	Screenshots, video, sound		
Intuitive Usability	Distance settings		
	Frequency filters (narrow band, 1/3-octave and octave)		
	Dynamic filter and low cut-off		
	3 scaling modes: off, auto, smart (crest factor)		



Tel.: +49 5241/21142-0 | Fax: +49 5241/21142-29 info@cae-systems.de | www.cae-systems.de

