## SOUNDCAM Product data



#### Highlights

- Real-time results at 100 fps
- Handheld device with IP54 protection
- Integrated object lighting
- 8 configurable buttons for fast control
- Analysis up to 24 kHz

#### Applications

- Machine acoustics
- Room- and building acoustics
- NVH. Squeak and Rattle measurement
- Leak test
- Noise localization



# SOUNDCAM

The First Handheld Sound Camera for Everyone





### What is SoundCam?

SoundCam is the first camera that images sound. The device locates sound sources in realtime and immediately displays the results on the screen. It is as easy to use as a smartphone.

The SoundCam can be used in a broad frequency range up to 24 kHz, which makes it suitable for a wide range of applications e.g. for product development in machinery and plant engineering, in the automotive and consumer goods industries.

The SoundCam visualizes complex acoustic information. Analyzing and understanding sound has never been easier!





	Н	ardware	
Physical Properties	Dimensions	34 x 34 x 9.5 cm (13.4 x 13.4 x 3.8 inch)	
	Weight	3 kg (7 lb)	
	Waterproof	IP54	
	Anti-theft system	Kensington lock	
	Battery	Life ~ 3.5 h; fully charged in 1.5 h	
	Tripod socket	1/4 inch	
	Buttons	8 configurable + power on/off	
	Operating temp	-20°C to 50°C (-4°F to 122°F)	
	Charging temp	0°C to 45°C (32°F to 113°F)	
	Storage temp	-30°C to 60°C (-22°F to 140°F)	
Display	Size	7 inch / 15.5 x 8.6 cm	
	Resolution	800 x 480 px	
	Touch	10 finger capacitive touch	
Fl	Processor	ARM A53 4x1.2 GHz with 1 GB RAM	
Embedded Controller	Internal storage	32 GB or 512 GB	
	OS	Linux for ARM	
	USB	For data export	
Interfaces	Ethernet	LAN (for running software on laptop/PC)	
	Audio	3.5 mm for headphones	
	Microphones	64 digital MEMS	
Sensors	Frequency range	Up to 24 kHz	
	Sample rate	48 kHz	
	Sound pressure	Max. 120 dB	
	Resolution	24 bit	
Optical Camera	Type	Digital	
	Resolution	320x240 (50fps) or 640x480 (16fps)	
	Lighting	4 LEDs	
	Aperture angle	70° (FoV horizontal)	
	Shutter	Global shutter	
	Battery	Li-ion rechargeable battery (48 Wh)	
Power	Input	19V with power adapter	
	Management	Smart: work and charge simultaneously	

	Software features		
OS	Linux (on SoundCam), Windows (for Laptop/PC)		
HMI	Touchscreen, headphones, buttons		
Protection	Password (unauthorized access protection)		
Online Performance	Up to 100 acoustic fps, up to 50 optical fps		
	Acoustic pictures, optical pictures, FFT and spectrogram Listen to local sound (broadband or frequency filtered)		
	Place marker while measuring		
	Buffer recording, trigger recording (SPL or frequency)		
	Long term measurements (average and peak-hold)		
	Time weighting: fast, slow, impulse		
Offline Features	View acoustic results frame by frame		
	Save and reload		
	Replay in real-time or slow motion		
	Listen to local sound		
Export	Screenshots, video, sound		
Intuitive Usability	Distance settings		
	Frequency filters (narrow band, 1/3-octave and octave)		
	Dynamic filter and low cut-off		
	3 scaling modes: off, auto, smart (crest factor)		



Tel.: +49 5241/21142-0 | Fax: +49 5241/21142-29 info@cae-systems.de | www.cae-systems.de

